

MOOVO ACCESSORIES TO COMPLETE THE AUTOMATION SYSTEM

Moovo accessories increase the safety and comfort of your home automation system



CUTTING EDGE

Moovo BUS Technology: connection of various devices such as photocells, selectors and flashing lights with just two wires



SAFE END FUNCTIONAL With digital keypad



SAFETY CODE Rolling code system




FLASHING SIGNAL LIGHT

High efficiency lenses and base with provision for mounting on walls or horizontal surfaces

(-	+

NO BLACK OUT

Motor with compartment for housing buffer battery (purchased separately)



THE CONVENIENCE OF A REMOTE CONTROL: MT4



Miniaturized 4 keys variable code transmitters with 433.92MHz transmission frequency and self-learning function

TOTAL SECURITY

ensured by the variable code with 18 billion billion combinations!

UNCLONABLE

the code varies with each transmission according to an algorithm that masks the code and does not show any relation with the following ones, which can only be recognized by the Moovo receiver: the same technology used in burglar systems

COMFORT AND WALL HIDDEN: MTI4



Recessed transmitter miniaturized 4 keys variable code with 433.92 MHz transmission frequency and self-learning function.

TOTAL SECURITY

ensured by the variable code with 18 billion billion combinations! Possibility of connecting up to 4 push buttons (optional) for cable control of automations.

COMFORT

four keys for the control of as many devices, transmission confirmation LED, key ring eyelet

VERY AUTONOMOUS AND LIGHTWEIGHT

with the two 3V lithium batteries

UNCLONABLE

the code varies with each transmission according to an algorithm that masks the code and does not show any relation with the following ones, which can only be recognized by the Moovo receiver: the same technology used in burglar systems

VERY AUTONOMOUS AND LIGHTWEIGHT

with the two 3 V lithium batteries

SAFE ACCESSORIES: MK - MKR



Alphanumeric selector with 4+1 keys with Moovo BUS Technology (MK) or via radio (MKR).

MOOVO BUS

Bus system to connect the alphanumeric selector with just two wires (MK).

TOTAL SECURITY

ensured by the variable code with 18 billion billion combinations (MKR)!

STURDY plastic casing, IP44

UNCLONABLE

the code varies with each transmission according to an algorithm that masks the code and does not show any relation with the following ones, which can only be recognized by the Moovo receiver: the same technology used in burglar systems (MKR).

EASY

direct and programmable command via Moovo Bus (MK).

KEYPAD THAT IS BACKLIT

in poor light conditions.

MORE SAFETY FOR YOUR AUTOMATION: MP - MPQ



Pair of photocells wall-mounted and auto-synchronized with Moovo BUS Technology (MP) or wire connection (MPQ).

EASY INSTALLATION

with the **Moovo Bus** system only two wires are required for connection of the main system components, and there is no need to follow any particular order! Quick, foolproof connections. Wasting time connecting to the photocell terminals is no longer necessary, simply connect the two wires at any point within the system.Convenient jumpers for selection of the required function. Up to 6 pairs of photocells can be installed without worrying about their proximity (MP).

AN ADDITIONAL DEVICE: MPT5



Photocell posts

EASY INSTALLATION With connector guide for easy and guickly photocell fixture.

MORE VISIBILITY AND SAFETY: MF



Adjustable flashing light with integrated aerial, 433.92 MHz frequency

EASY INSTALLATION

can be mounted in any position using the base designed for wall or horizontal installation

MAXIMUM SECURITY

High efficiency lenses optimise visibility

MAXIMUM SECURITY electronics protected by a second plastic

casing to prevent damage during installation. The antidazzle circuit protects you from blinding glares generated by the sun

or other powerful light sources

COMFORT

very simple alignment thanks to the LED signal with proportional flashing

STURDINESS

extra thick polycarbonate body

COMFORT

easy accessibility and replacement of the powerful lamp used in the automotive industry


DURABILITY

shock-resistant polycarbonate structure

MOOVO BUS

new Bus system for the connection of various devices such as photocells, selectors and flashing lights with just two wires

NO MORE BLACKOUT: MB - ME



Emergency battery at 12 V (MB) for gates motors or at 24 V (ME) for garage doors motors.

NO BLACK OUT Buffer battery for emergency power supply

MOOVO KITS

XW432BE




Kit for the automation of a residential double gate up to 1.80 m in wigth and weighing up to 180 kg per gate; high max 2 m. Motor with compartment for housing buffer battery

TS432B



Kit for the automation of a sectional door up to 3.5 m in width and up to 2.12 m high or sprung or counterweight overhead doors up to 3.5 m in width and up to 2.6 m high. Guide made up of 3 870 mm sections.





Kit for the automation of a residential double gate up to 2.5 m in wigth and weighing up to 250 kg per gate; high max 2 m. Motor with compartment for housing buffer battery

TS432BE



Kit for the automation of a sectional door up to 3.5 m in width and up to 2.12 m high or sprung or counterweight overhead doors up to 3.5 m in width and up to 2.6 m high. Guide made up of 3 870 mm sections. Motor with compartment for housing buffer battery

XA432BE



Kit for the automation of a residential double gate up to 1.8 m in wigth and weighing up to 250 kg per gate; high max 2 m. Motor with compartment for housing buffer battery

LN432BE



Kit for the automation of a residential double gate up to 5 m in wigth and weighing up to 300 kg. Motor with compartment for housing buffer battery



Oderzo TV, Italy Tel. +39 0422 20 21 09 Fax +39 0422 85 35 85 www.moovo.com